

Liquid Drainers ID Charts



Armstrong Liquid Drainers															
Illustration	Type	Flow Direction	Connection Type	Max. Allow. Press. psig	TMA °F	Body Material	Model	Max. Oper. Press. psig	Connection Size						Located on Page
									1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	
	Series 1-LDC See-Thru Free Floating Lever Drain Traps Capacities to 1,500 lb/hr	↓	Screwed	150	150	Nylon Cap Polysulfone Body	1-LDC	150	●	★★					LD-34
	Series 200 BVSU Inverted Bucket Drain Traps Capacities to 7,000 lb/hr	↑	Screwed	250	450	ASTM A48 Class 30 Cast Iron	211 212 213	250	●	●	●				LD-36
	Series 800 BVSU Inverted Bucket Drain Traps Capacities to 7,000 lb/hr	→	Screwed	250	450	ASTM A48 Class 30 Cast Iron	800 811 812 813	150 250 250 250	●	●	●				LD-35
	Series 880 BVSU Inverted Bucket Drain Traps Capacities to 7,000 lb/hr	→	Screwed	250	450	ASTM A48 Class 30 Cast Iron	880 881 882 883	150 250 250 250	●	●	●		●		
	Series 300 BVSU Inverted Bucket Drain Traps Capacities to 7,000 lb/hr	↑	Screwed Socketweld Flanged†	600 1,080	650 650	ASTM A105 Forged Steel	312 313	600	●	●	●				LD-36
	Series 900 BVSU Inverted Bucket Drain Traps Capacities to 7,000 lb/hr	→	Screwed Socketweld Flanged†	600	650	ASTM A216 WCB Cast Steel	981 983	300 600	●	●	●				
	Series 1, 2, 3, 6 Free Floating Lever Drain Traps Capacities to 49,000 lb/hr	↓	Screwed	300 250	200 450	ASTM A48 Class 30 Cast Iron	1-LD 2-LD 3-LD 6-LD	300 250	★ ●	●	●			●	LD-38
	Series 11, 22, 13 Free Floating Lever Drain Traps Capacities to 9,500 lb/hr	↓	Screwed Socketweld Screwed Socketweld (22 and 13 Series Only)	500 or 440 600 or 475 570 or 490	100 or 500 100 or 500 100 or 500	304-L Stainless Steel	11-LD†† 22-LD 13-LD	400 533 570	●	★★ ●				●	LD-39

★ 1/4" outlet connection.

















★★ 1/2" outlet connection.

†Flange selection may limit pressure and temperature rating.

††Side connection not available.

















Armstrong® Liquid Drainers ID Charts

Armstrong Liquid Drainers															
Illustration	Type	Flow Direction	Connection Type	Max. Allow. Press. psig	TMA °F	Body Material	Model	Max. Oper. Press. psig	Connection Size						Located on Page
									1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	
	180-LD/181-LD Free Floating Lever Drain Traps Capacities to 1,100 lb/hr		Screwed Socketweld	500 or 440	100 or 500	304L Stainless Steel	180-LD	229	●					LD-40	
							181-LD	350		●					
	Series 30 Free Floating Lever Drain Traps Capacities to 42,000 lb/hr		Screwed Socketweld Flanged†	600 or 500	100 or 750	ASTM A105 Forged Steel	32-LD	600	●	●				LD-42	
				1,000 or 600	100 or 750		33-LD	900	●	●	●				
				1,000 or 600	100 or 750		36-LD	1,000				●	●		
	Series 21 Fixed Pivot Drain Trap Capacities to 2,700 lb/hr		Screwed	250	450	ASTM A48 Class 30 Cast Iron	21	250	●	●					
	Series 21-312 Fixed Pivot Drain Traps Capacities to 3,900 lb/hr		Screwed Socketweld Flanged†	600 or 500	100 or 750	ASTM A105 Forged Steel	21-312	74	●	●			LD-43		
							21-312V	600	●	●					
	Series 71-A Snap Action Drain Trap Capacities to 1,950 lb/hr		Screwed	250	450	ASTM A48 Class 30 Cast Iron	71-A	250		●	●				
	Series 71-315 Snap Action Drain Trap Capacities to 1,950 lb/hr		Screwed Socketweld Flanged†	1,000 or 600	100 or 750	ASTM A105 Forged Steel	71-315	1,000		●	●	●			
	Series 2300 High Leverage Spring-Loaded Float Type Drain Trap Capacities to 14,500 lb/hr		Screwed Socketweld Flanged†	1,000 or 600	100 or 750	ASTM A105 Forged Steel	2313-HLS		●	●	●			LD-46	
							2315-HLS	1,000			●	●	●		
							2316-HLS					●	●		
	Series 2400 High Leverage Spring-Loaded Float Type Drain Traps Capacities to 16,250 lb/hr		Screwed Socketweld Flanged†	1,500 or 900	100 or 850	ASTM A182 Gr. F22 Forged Steel	2413-HLS	1,500	●	●	●				
				1,800 or 900	100 or 900		2415-HLS	1,800			●	●	●		
							2416-HLS	1,600				●	●		

†Flange selection may limit pressure and temperature rating.

Liquid Drainers ID Charts

Armstrong Liquid Drainers																
Illustration	Type	Flow Direction	Connection Type	Max. Allow. Press. psig	TMA °F	Body Material	Model	Max. Oper. Press. psig	Connection Size							Located on Page
									1/2"	3/4"	1"	1-1/2"	2"	2-1/2"	3"	
	Series 2500/2600 High Leverage Spring-Loaded Float Type Drain Traps Capacities to 11,000 lb/hr		Screwed Socketweld Flanged†	2,120 or 1,700	100 or 900	ASTM A182 Gr. F22 Forged Steel	25133G HLS	2,120		●	●	●				LD-46
				2,520 or 2,000	100 or 900		25155G HLS	2,520			●	●	●			
				3,700 or 3,000	100 or 900		26155G HLS	3,700				●	●			
	Series 2, 3, 6 Free Floating Lever Dual Gravity Drain Traps Capacities to 40,000 lb/hr		Screwed	250	450	ASTM A48 Class 30 Cast Iron	2-DG	190	●	●					LD-48	
							3-DG	250		●	●					
							6-DG	250				●	●			
	Series 30 Free Floating Lever Dual Gravity Drain Traps Capacities to 40,000 lb/hr		Screwed Socketweld Flanged†	600 or 500	100 or 750	ASTM A105 Forged Steel	32-DG	325	●	●	●				LD-49	
				1,000 or 600	100 or 750		33-DG	700		●	●					
				1,000 or 600	100 or 750		36-DG	1,000				●	●			
	Series JD&KD Ultra-Capacity Drain Traps Capacities to 302,000 lb/hr		Screwed	300	650	ASTM A48 Class 30 Cast Iron	JD8	300*						●	LD-49	
							KD8						●			
							KD10						●			
							KD12						●			
	Series L&M Ultra-Capacity Drain Traps Capacities to 700,000 lb/hr		Screwed	250	450	ASTM A48 Class 30 Cast Iron	L8	250*					●	LD-49		
							L10						●			
							M12						●			
	Series LS&MS Ultra-Capacity Drain Traps Capacities to 700,000 lb/hr		Screwed Socketweld Flanged†	450	650	ASTM A216 WCB Cast Steel	LS8	450*					●	LD-49		
							LS10						●			
							MS12						●			
	ADP-1 Pneumatically Operated Liquid Drainer Capacities to 1.5 lb liquid per cycle		Screwed	180	150	Aluminum ASTM B221 6061-T6511	ADP-1	180		●					LD-53	

*For different specific gravities, see table LD-33 on page LD-49.

†Flange selection may limit pressure and temperature rating.