











Armstrong® Strainers ID Charts

Illustration	Model	Connection Size	Connection Type	Body Material	Pressure Temperature Ratings		Located on Page	
					Steam Non-shock	Cold Non-shock		
	CA	1/2", 3/4", 1", 1-1/4", 1-1/2", 2"	Screwed	Cast Iron ASTM-A48 Class 30	250 psig @ 406°F	400 psig @ 150°F	S-7	
	A	2-1/2", 3"					S-7	
	A	2"	125 Flanged		125 psig @ 353°F	175 psig @ 150°F	S-8	
	A	2-1/2" - 10"					S-8	
	A	2"	250 Flanged		250 psig @ 400°F	400 psig @ 150°F	S-8	
	A	2-1/2" - 8"					S-8	
	B	1/2", 3/4", 1"	Screwed & Socketweld 900 lb		Cast Carbon Steel ASTM-A216 Gr. WCB	1,635 psig @ 609°F	2,220 psig @ 100°F	S-9
	B	1-1/4", 1-1/2", 2", 3"	Screwed & Socketweld 600 lb					1,135 psig @ 562°F
	B	1/2", 3/4", 1"	Class 150 Flanged	205 psig @ 390°F		285 psig @ 100°F	S-10	
	B	1-1/4", 1-1/2", 2", 3"					S-10	
	B	4", 6"					S-10	
	B	1/2", 3/4", 1"	Class 300 Flanged	605 psig @ 490°F		740 psig @ 100°F	S-10	
	B	1-1/4", 1-1/2", 2", 3"					S-10	
	B	4", 6"					S-10	
	B	1/2", 3/4", 1"	Class 600 Flanged	1,135 psig @ 562°F	1,480 psig @ 100°F	S-10		
	B	1-1/4", 1-1/2", 2", 3"				S-10		
B	4"	S-10						
	C	1/2", 3/4", 1"	Screwed & Socketweld 1,500 lb	Cast Chrome Moly Steel ASTM-A217 Gr. WC6	2,090 psig @ 643°F	3,000 psig @ 100°F	S-11	
	C	1-1/4", 1-1/2", 2"					2,515 psig @ 670°F	3,600 psig @ 100°F
	C	1/2", 3/4", 1"	Class 1,500 Flanged		2,090 psig @ 643°F	3,000 psig @ 100°F	S-11	
	C	1-1/4", 1-1/2", 2"					2,515 psig @ 670°F	3,600 psig @ 100°F
	D	1/2", 3/4", 1", 1-1/4", 1-1/2", 2"	Socketweld 2,500 lb		Forged Steel ASTM-A182 Gr. F22	2,500 psig @ 1,025°F	6,000 psig @ 100°F	S-12

Strainers

Strainers ID Charts

Illustration	Model	Connection Size	Connection Type	Body Material	Pressure Temperature Ratings		Located on Page
					Steam Non-shock	Cold Non-shock	
	E	1/2", 3/4", 1"	Screwed & Socketweld 1,500 lb	Cast Stainless Steel ASTM-A351 Gr. CF8M	2,090 psig @ 643°F	3,000 psig @ 100°F	S-13
	E	1-1/4", 1-1/2", 2", 3"	Screwed & Socketweld 600 lb		935 psig @ 538°F	1,140 psig @ 100°F	S-13
	E	1/2", 3/4", 1"	Class 150 Flanged		200 psig @ 386°F	275 psig @ 100°F	S-14
	E	1-1/2", 2", 3"			S-14		
	E	4", 6"			S-14		
	E	1/2", 3/4", 1"	Class 300 Flanged		495 psig @ 467°F	720 psig @ 100°F	S-14
	E	1-1/2", 2", 3"			S-14		
	E	4", 6"			S-14		
	E	1/2", 3/4", 1"	Class 600 Flanged		935 psig @ 540°F	1,440 psig @ 100°F	S-14
	E	1-1/2", 2", 3"			S-14		
E	4"	S-14					
	F	1/2", 3/4", 1", 1-1/4"	Screwed 300 lb	Cast Bronze ASTM-B62	300 psig @ 422°F	500 psig @ 150°F	S-15
	F	1-1/2", 2"					S-15